



\*\*\*spare part\*\*\* SIMATIC S7-1500, TM NPU, technology module for applications with artificial intelligence, 1x Ethernet, 1x USB, 1x SD

General information	
Product type designation	TM NPU
HW functional status	04
Firmware version	V2.0
<ul style="list-style-type: none"> <li>FW update possible</li> </ul>	Yes
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; I&M0 to I&M3
<ul style="list-style-type: none"> <li>Artificial intelligence/processing of neural networks</li> </ul>	Yes
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated from version</li> </ul>	STEP 7 V17 or higher with HSP
<ul style="list-style-type: none"> <li>STEP 7 configurable/integrated from version</li> </ul>	- / -
<ul style="list-style-type: none"> <li>PROFIBUS from GSD version/GSD revision</li> </ul>	- / -
<ul style="list-style-type: none"> <li>PROFINET from GSD version/GSD revision</li> </ul>	GSDML V2.35
Installation type/mounting	
Mounting position	Horizontal, vertical
Rail mounting	Yes
Control cabinet installation	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Short-circuit protection	Yes
Mains buffering	
<ul style="list-style-type: none"> <li>Mains/voltage failure stored energy time</li> </ul>	5 ms
Input current	
Current consumption (rated value)	0.35 A; 24 V input voltage, USB load of 800 mA, 25 °C ambient temperature
Current consumption, max.	0.6 A
Inrush current, max.	3 A
I <sup>2</sup> t	0.17 A <sup>2</sup> ·s
Power	
Power consumption from the backplane bus	0.65 W
Power consumption from the backplane bus (balanced)	1.1 W
Power loss	
Power loss, typ.	4.6 W
Processor	
Processor type	Myriad X 2x LEON processor with 700 MHz
Address area	
Address space per module	

• Inputs	254 byte; +2 bytes QI and application-specific status bytes
• Outputs	254 byte; +2 application-specific control bytes
<b>Interfaces</b>	
Number of Ethernet interfaces	1
Number of USB interfaces	1
SD card slot	Yes
<b>1. Interface</b>	
Interface type	Ethernet
Isolated	Yes; 1500 V AC (type test)
supported image format	YUYV422, UYVY422
supported image resolution	1 280 x 1 024, 1 280 x 720, 640 x 480
<b>Interface types</b>	
• RJ 45 (Ethernet)	Yes
• Number of ports	1
• integrated switch	No
<b>2. Interface</b>	
Interface type	USB
Isolated	Yes; 500 V DC (type test)
supported image format	YUYV422
supported image resolution	1 280 x 720
<b>Interface types</b>	
• USB	Yes; only for commissioning and test purposes
• Number of ports	1
• Output current of the interface, max.	900 mA
<b>Interface types</b>	
<b>RJ 45 (Ethernet)</b>	
• 1000 Mbps	Yes
<b>USB port</b>	
• USB specification	USB 3.1
• Design of the USB ports	USB type A socket
<b>Protocols</b>	
<b>Protocols (Ethernet)</b>	
• GigE Vision	Yes; V2.1
<b>Web server</b>	
• supported	Yes; only for Debug purposes. Should be disabled during normal operation.
<b>Interrupts/diagnostics/status information</b>	
Status indicator	Yes
Alarms	No
Diagnostics function	Yes
<b>Diagnostics indication LED</b>	
• RUN LED	Yes
• ERROR LED	Yes
• MAINT LED	Yes
• LINK LED	Yes
• Monitoring of the supply voltage (PWR-LED)	Yes
<b>Isolation</b>	
Isolation tested with	1 500 V AC between Ethernet and functional ground
<b>Ambient conditions</b>	
<b>Ambient temperature during operation</b>	
• horizontal installation, min.	-25 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	-25 °C
• vertical installation, max.	40 °C
<b>Ambient temperature during storage/transportation</b>	
• min.	-40 °C
• max.	70 °C
<b>Altitude during operation relating to sea level</b>	
• Installation altitude above sea level, max.	2 000 m

Decentralized operation	
to SIMATIC S7-300	Yes
to SIMATIC S7-400	Yes
to SIMATIC S7-1200	Yes
to SIMATIC S7-1500	Yes
to standard PROFIBUS master	No
to standard PROFINET controller	No
Dimensions	
Width	35 mm
Height	147 mm
Depth	129 mm
Weights	
Weight, approx.	400 g

Classifications			
		Version	Classification
	eClass	14	27-24-22-05
	eClass	12	27-24-22-05
	eClass	9.1	27-24-22-05
	eClass	9	27-24-22-05
	eClass	8	27-24-22-05
	eClass	7.1	27-24-22-05
	eClass	6	27-24-22-05
	ETIM	10	EC001422
	ETIM	9	EC001422
	ETIM	8	EC001422
	ETIM	7	EC001422
	IDEA	4	3567
	UNSPSC	15	32-15-17-05

**Approvals / Certificates**

General Product Approval



[Miscellaneous](#)



General Product Approval

EMV

[China RoHS](#)



last modified:

10/23/2025