



*** spare part *** SIMATIC PG, USB external prommer

Figure similar

General information																																											
Design of the programming device	Desktop device																																										
Display																																											
Design of display	without																																										
Supply voltage																																											
Design of the power supply	12 V DC, 1.25 A (via power supply included 100 - 240 V / 50 - 60 Hz / 400 - 200 mA)																																										
Ambient conditions																																											
Ambient temperature during operation																																											
• min.	5 °C																																										
• max.	40 °C																																										
Ambient temperature during storage/transportation																																											
• min.	-20 °C																																										
• max.	60 °C																																										
Dimensions																																											
Width	172 mm																																										
Height	40 mm																																										
Depth	121 mm																																										
Weights																																											
Weight, approx.	400 g																																										
Classifications																																											
	<table border="1"> <thead> <tr> <th></th> <th>Version</th> <th>Classification</th> </tr> </thead> <tbody> <tr> <td>eClass</td> <td>14</td> <td>19-20-05-92</td> </tr> <tr> <td>eClass</td> <td>12</td> <td>19-20-05-92</td> </tr> <tr> <td>eClass</td> <td>9.1</td> <td>19-20-05-92</td> </tr> <tr> <td>eClass</td> <td>9</td> <td>19-20-05-92</td> </tr> <tr> <td>eClass</td> <td>8</td> <td>19-20-05-92</td> </tr> <tr> <td>eClass</td> <td>7.1</td> <td>27-36-04-92</td> </tr> <tr> <td>eClass</td> <td>6</td> <td>27-36-04-92</td> </tr> <tr> <td>ETIM</td> <td>10</td> <td>EC002584</td> </tr> <tr> <td>ETIM</td> <td>9</td> <td>EC002584</td> </tr> <tr> <td>ETIM</td> <td>8</td> <td>EC002584</td> </tr> <tr> <td>ETIM</td> <td>7</td> <td>EC002584</td> </tr> <tr> <td>IDEA</td> <td>4</td> <td>6628</td> </tr> <tr> <td>UNSPSC</td> <td>15</td> <td>32-15-17-07</td> </tr> </tbody> </table>		Version	Classification	eClass	14	19-20-05-92	eClass	12	19-20-05-92	eClass	9.1	19-20-05-92	eClass	9	19-20-05-92	eClass	8	19-20-05-92	eClass	7.1	27-36-04-92	eClass	6	27-36-04-92	ETIM	10	EC002584	ETIM	9	EC002584	ETIM	8	EC002584	ETIM	7	EC002584	IDEA	4	6628	UNSPSC	15	32-15-17-07
	Version	Classification																																									
eClass	14	19-20-05-92																																									
eClass	12	19-20-05-92																																									
eClass	9.1	19-20-05-92																																									
eClass	9	19-20-05-92																																									
eClass	8	19-20-05-92																																									
eClass	7.1	27-36-04-92																																									
eClass	6	27-36-04-92																																									
ETIM	10	EC002584																																									
ETIM	9	EC002584																																									
ETIM	8	EC002584																																									
ETIM	7	EC002584																																									
IDEA	4	6628																																									
UNSPSC	15	32-15-17-07																																									

General Product Approval



[Manufacturer Declaration](#)



General Product Approval

EMV



last modified:

5/22/2024